


SHARP®


空氣清新機 直立式

使用說明書



High-Density 7000

FU-Y30A-W



多謝您購買銳寶空氣清新機。
操作之前，請仔細閱讀說明書，以便正確地
使用空氣清新機。閱讀後請妥善保存此說明
書，以便日後翻閱。

※Plasmacluster™“離子簇”是SHARP株式會社的商標

香港電器安全規格
(國際電工委員會規格符合)

目錄

頁數

請務必閱讀

- 重要安全事項
- 警告
- 操作的注意事項
- 安裝指南
- 安裝位置
- 過濾網指南

C-2	1
C-3	2
C-4	3
C-5	4

使用之前

- 準備工作
- 各部分名稱
- 安裝過濾網

C-7	1
C-8	2
C-9	3

操作方法

- 操作方法
- 日常保養
- 主機、背板、過濾網
- 過濾網更換指南
- 多功能HEPA除臭過濾網

C-10	1
C-11	2
C-12	3
C-13	4
C-14	5
C-15	6

檢查事項

- 故障時的檢查事項

C-16	1
------	---

規格

- 規格

C-17	1
------	---

特點

- 特點

C-18	1
------	---

本產品專為家庭用戶設計，而非為商業用戶設計

SHARP®
SHARP CORPORATION

TINS-A153SRZ ①

使用說明書

空氣清新機 FU-Y30A-W

重要安全事項

使用電器時，必須遵守基本安全預防措施。包括以下各方面：

警告—為了減少觸電、火災或受傷等危險：

- 在使用空氣清新機之前請閱讀所有注意事項。
- 只能使用220V插座。
- 如果電源線或插頭已經損壞，或者牆上的電源插座已鬆脫，請勿使用空氣清新機。
- 定期清除電源插頭上的灰塵。
- 請勿將手指或異物插入吸氣口或吹出口。
- 當拔掉電源插頭時，必須緊握插頭而不要拉扯電源線。否則可能導致觸電或因短路引起火災。
- 手濕時請勿拔插電源插頭。
- 請勿在氣體設備或壁爐附近使用空氣清新機。
- 清潔本機或不使用本機時，請將插頭從牆上的電源插座上拔掉。否則可能導致因絕緣不良而引起觸電或因短路而引起火災。
- 如果電源線損壞，必須由製造商或其代理、經賣公司特約維修中心或具有同等資格的人員負責更換，以免發生危險。
- 當使用噴發殺蟲劑時請勿使用本機，或房間內有油渣、焚香時的煙、點煙時的火苗、空氣中有化學氣味或浴室等濕氣很重的地方也不要使用本機。
- 清潔空氣清新機時請加以小心。具強力腐蝕性的清潔劑會損壞本機表面。
- 除未得到監護人或負責其安全人士的適當監督或指導，否則，此機器不適合身體官能或心智能力退化者，或缺乏操作經驗和知識的人士(包括兒童)使用。
- 兒童應受到適當監督以確保不會以此機器作玩具。
- 只有經特約維修人員方可維修本空氣清新機，當需要調校、修理或出現問題時，請聯絡就近的維修中心。

注意—收音機或電視干擾

如果本空氣清新機對收音機或電視接收造成干擾，請嘗試以下列其中一項或多項措施修正干擾：

- 重新調整或重新放置接收天線。
- 增加空氣清新機和收音機/電視接收器的距離。
- 將本設備的電源與接收器的電源連接到不同的插座。
- 如需協助，請聯絡經銷商或專業的收音機/電視技術人員。

操作的注意事項

- 請勿堵塞吸氣口和吹出口。
- 使用本機時，不要靠近或放在熱源物體上(如爐灶、暖爐或可能接觸到蒸氣的場所)。
- 使用時請勿平放本機。
- 移動本機時，必須一直緊握主機兩側的手柄。
- 移動時若握着面板可能導致面板脫落，掉落主機，造成人身傷害。
- 請勿在沒有安裝過濾網的情況下操作本機。
- 請勿清洗和重用多功能HEPA除臭過濾網。
- 只能使用軟布清潔本機表面。
- 否則本機可能會損壞或破裂。

警告 如果電源線損壞，為了避免發生危險，必須由製造商、經賣公司或特約維修中心或具有相同資格的人員來更換。

安裝指南


- 操作本機時，請將本機放於帶有電線的設備(如電視機、收音機或時鐘)至少2米以外的地方，以防產生電波干擾。
- 請勿安裝在窗簾等物件可能會接觸到吸氣口或吹出口的地方。否則該物件可能會被污染或導致本機故障。
- 請勿安裝在由於溫度劇烈變化而導致本機直接暴露於冷凍環境的地方。
- 在0至35度室溫的適當情況下使用。
- 安裝必須穩固，且通風良好。
- 把本機放置在鋪有厚地毯的地方時，可能導致本機輕微震動。
- 請勿安裝在會產生黑煙的地方(如廚房等)。
- 否則可能會導致本機表面破裂。

安裝位置

- 確保離子簇可以順利吹送到房間的各個角落。

周圍保持一定空間

請在約0°C ~ 35°C的房間內使用。



- 請勿傾斜或橫向放置本機，請垂直放置本機。
- 若將本機放置在地毯等柔軟的地方，可能會產生輕微震動。

過濾網指南


- 遵照說明書指示，了解正確保養和清潔過濾網的方法。

準備工作


警告 如果電源線損壞，為了避免發生危險，必須由製造商、經銷公司的特約維修中心或具有相同資格的人員來更換。

各部分名稱

操作面板




前面



C-4

各部分名稱

背面



C-5

準備工作

請必須在電源插頭插入插座之前進行。

安裝過濾網


請務必將在主機內過濾網的塑膠包裝袋拆除，並將過濾網重新安裝在機器上。

安裝過濾網

1 取出過濾網


1 拆下背板
按下上方的扣鉤，
拆下背板

2 將過濾網從塑膠袋中取出




2 安裝過濾網

1 將過濾網安裝在主機內，使附有頁片的一面朝向外
※ 請勿以反方向安裝過濾網，否則將影響本機正常操作。




2 安裝背板

將背板插入主機下方的孔內，然後緊扣上方的扣鉤。




3 記錄開始使用的日期

在保養標籤上記錄過濾網開始使用的日期。



操作方法

主機操作




電源開/關鍵

- 開始操作（「嗶」聲音，操作開始。）
- 停止操作（較長的「嗶」聲音，操作停止。）

風速切換鍵

- 每觸按一次，風速即按下列的順序切換。



離子簇開/關鍵

- 可以設定離子簇的開/關。
- 在離子簇「開」狀態下，離子簇指示燈將點亮。

日常保養

主機・背板・過濾網

主機

約1個月1次

- 請用柔軟的布擦拭主機表面。
- 污漬嚴重時，請用含溫水(40°C)的濕布擦拭，不可直接用水淋洗主機。
- 請勿使用下列揮發性物料或清潔劑。(揮發油、稀釋劑、拋光粉、酒精、石油等)
- 這可能會損壞主機表面。

背板

約2週1次

- 請用吸塵機吸走，附着在背板上的灰塵。


髒污嚴重時

- 請放在溶解有廚房用清潔劑的水中或者於溫水(40°C以下)中浸洗(約10分鐘)。
- 對其進行充分地清洗，保證沒有清潔劑殘留。
- 除去多餘水分，徹底晾乾。

過濾網


約3個月1次

- 吸掃
- 不能水洗



從主機上拆下過濾網，用吸塵機沿着過濾網的紋路吸取表面的灰塵。

- 為免弄污四周，清潔時請在過濾網下面鋪墊報紙等。
- 吸掃時，請勿用力過度，過濾網可能會受到損壞。




△警告
在保養時，請務必停止操作，並從電源插座上拔下電源插頭。尾端避免觸電和受傷，請勿以濕手插入或拔出電源插頭。

日常保養

△警告
在保養時，請務必停止操作，並從電源插座上拔下電源插頭。為避免觸電和受傷，請勿以濕手插入或拔出電源插頭。

過濾網更換指南

2年1次※



注意

- 為了不弄髒周圍環境，更換時請用報紙鋪墊。
- 請根據使用說明書中「安裝過濾網」的相關內容進行更換。(C-6)
- 在保養標籤上記錄過濾網開始使用的日期。
- 根據居住地區的垃圾分類方法丟棄過濾網。


※過濾網壽命的計算依據：

根據「日本電機工業會規格-JEM1467」標準，以每天燃點5支香煙，而集塵/除臭效能比初次使用時減少一半來計算，過濾網的壽命約為2年。實際更換期取決於主體使用時間長短及其安裝地點。過濾網為消耗品，保養期內也需要購買。

- 多功能HEPA
除臭過濾網的材質

- 濾材：聚丙烯
- 框材：聚亞胺
- 脫臭劑：活性炭

多功能HEPA除臭過濾網



可以去除的物質

- 花粉、過敏原
(細菌的糞便・屍體)
- 病毒
- 霉菌
- 灰塵
- 香煙煙味(粒子)
- 寵物的毛髮
- 香煙煙味(異味)
- 廁所的異味
- 垃圾的異味
- 寵物的異味

無法去除的物質

- 有害氣體成分(香煙的一氧化碳等)
- 一直持續產生的異味成分
(甲醛等建築材料異味・寵物異味等)

故障時的檢查事項

下列故障可能並不是故障，在委託修理之前請再次進行確認和檢查。

症狀

請進行檢查

難以去除異味、煙霧

- 過濾網是否仍在塑膠袋裏嗎？
→請很緩慢地準備工作，一經把過濾網從塑膠袋裏拿出來。

C-6

出風口吹出的風有異味。

- 過濾網可能已經嚴重髒污。
→請更換過濾網。
- 由於離子簇會產生微量的臭氧離子，出風口有時會有異味，但只是微量，對健康沒有影響。
- 是否在氣味強烈的房間內使用？
- 如果在香煙和燒肉等強烈氣味下使用，數週或數月內過濾網可能會產生異味。此時需要更換過濾網。
- 如果在上述情況下使用，建議經常對房間進行換氣。

從主機中發出“噠”的聲音？

- 產生離子簇時的聲音，並非異常。
- 聲音的大小將會視乎使用環境和運行模式的不同而時大時小，有時甚至聽不到，但離子簇的效果是完全相同的。

規格

型號	號	型號
FU-V30A-W		
適用面積(平方米)	220呎特～50呎茲	
風速模式	21	
空氣流量(立方米/小時)	最大	標準
額定耗電量(瓦)	180	120
噪音(分貝)	35	26
外形尺寸(毫米)	45	34
重量(公斤)	356(開)X180(深)X510(高)	約5.0
電源線長度(米)	2.0	

更換用過濾網型號(另購配件)：FZ-V180SFS-HK

ENGLISH

特點

「離子簇」空氣淨化技術

離子簇空氣淨化技術利用離子產生器製造及釋放與自然環境相同的正離子及負離子。離子簇是實質獨有的空氣淨化技術，可以有效去除空氣中的病毒^{*1}、細菌、霉菌^{*2}及過敏原^{*3}，例如塵蟎屍體或排泄物。這技術已得到日本及世界各國的第三方機構驗證。高濃度的離子簇可以去除依附在窗簾或沙發上的香煙煙味^{*4}。若將衣服懸掛在出風口直接吹送的位置，可以去除附在衣服上的汗味至不易察覺水平。

※1 RETROSCREEN VIROLOGY LTD. (英國)

在1立方米的箱子內測定對空氣中病毒的去除率。

※2 (財) 石川縣預防醫學協會 (日本)

在約13平方米的房間內用空氣抽樣方法對浮游霉菌進行測定。

※3 廣島大學大學院先端物質科學研究所 (日本)

在約13平方米的房間內測定對浮游塵蟎的作用。

※4 (財) 日本紡織檢查協會 (日本)

對附有異味的布片測定除臭效果。

FEATURES

“Plasmacluster” Air Purifying Technology

Plasmacluster air purifying technology uses plasma discharge to generate and emits the same positive and negative ions that occur in nature, i.e. Plasmacluster ions. This is a unique air purifying technology of SHARP CORPORATION for breaking down and inactivating virus^{*1}, bacteria, molds^{*2} and allergens^{*3}, such as feces or corpses of mites, suspended in the air. It has been substantiated by third-party organizations both in Japan and overseas. High density of Plasmacluster ions in the air can remove cigarette smell trapped in curtains or sofas^{*4}. When hanging clothes directly to the air outlet of the unit generating Plasmacluster ions, the smell of sweat can be reduced to a virtually imperceptible level.

*1 Retroscreen Virology, Ltd., London, UK

Measurement of ratio of viruses eliminated from the air in a 1m³ box

*2 Ishikawa Health Service Association, Japan

Measurement of molds and bacteria with an air sampler in a 13m² area.

*3 Graduate School of Advanced Sciences of Matter, Hiroshima University, Japan

Measurement of action on the potential allergens of aerial mites in a 13m² undecanted room


*4 Japan Spinners Inspecting Foundation, Japan

Evaluation of deodorizing effect on odor-imbued fragments of cloth

SHARP®


AIR PURIFIER **FREE STANDING**

OPERATION MANUAL



High-Density 7000

FU-Y30A-W



Plasmacluster is a trademark of Sharp Corporation.

CONTENTS

IMPORTANT SAFETY INSTRUCTIONS E-2

- WARNING E-2
- CAUTIONS CONCERNING OPERATION E-3
- INSTALLATION GUIDELINES E-3
- INSTALLATION SPACE E-3
- FILTER GUIDELINES E-3

PARTS NAMES E-4

- CONTROL PANEL E-4
- ILLUSTRATIVE DIAGRAM E-4

PREPARATION E-6

- FILTER INSTALLATION E-6

OPERATION E-8

- MAIN UNIT OPERATION E-8

CARE AND MAINTENANCE E-9

- MAIN UNIT E-9
- BACK PANEL E-9
- FILTER REPLACEMENT GUIDELINES E-10
- MULTI-FUNCTIONAL HEPA DEODORIZING FILTER E-10

TROUBLESHOOTING E-11

SPECIFICATIONS E-11

FEATURES C-12

Please read this manual carefully for the correct usage information. Before using this product, be sure to read the section: "Important Safety Instructions." After reading this manual, retain it in a convenient location for future reference.

IMPORTANT SAFETY INSTRUCTIONS

When using electrical appliances, basic safety precautions should be followed, including the following:

WARNING

- To reduce the risk of electric shock, fire or injury to persons:

- Read all instructions before using the air purifier.
- Use only a 220 volt outlet with a polarized receptacle.
- Do not use the air purifier if the power cord or plug is damaged or the connection to the wall outlet is loosened.
- Periodically remove dust from the power plug.
- Do not insert fingers or foreign objects into the air inlet or air outlet.
- When removing the power plug, always hold the plug and never pull on the cord.
- Electric shock and/or fire from short circuit may occur.
- Do not remove the plug when your hands are wet.
- Do not use this air purifier near gas appliances or fireplaces.
- Remove the power plug from the wall outlet before cleaning the unit and when not using the unit.
- Electric shock from bad insulation and/or fire from short circuit may occur.
- If the power cord is damaged, it must be replaced by the manufacturer, its service agent, Sharp Authorized Service Centre or similar qualified person in order to avoid hazard.
- Do not operate when using aerosol insecticides or in rooms where there is oily residue, incense, sparks from lit cigarettes, chemical fumes in the air or in very high humidity condition, such as a bathroom.
- Be cautious when cleaning the air purifier. Strong corrosive cleansers may damage the exterior.
- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
- Children should be supervised to ensure that they do not play with the appliance.
- Only Sharp Authorized Service Centre should service this air purifier. Contact the nearest Service Centre for any problems, adjustments, or repairs.

NOTE

- Radio or TV Interference

If this air purifier should cause interference to radio or television reception, try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation distance between the air purifier and radio/TV receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

CAUTIONS CONCERNING OPERATION

- Do not block the air inlet and air outlet.
 - Do not use the unit near or on hot objects, such as stoves or heaters or where it may come into contact with steam.
 - Do not lay the unit down when using.
 - Always hold the handle on the two side of the unit when moving it.
- Holding the front panel when carrying may cause it to detach, thus dropping the unit and resulting in injury.


- Do not operate the unit without the filter.
 - Do not wash and reuse filter.
 - It not only does not improve filter performance, it may cause electric shock or malfunction.
 - Clean the exterior with a soft cloth only.
- Otherwise, the unit surface may be damaged or cracked.

INSTALLATION GUIDELINES

- During the operation of the product, please place the unit at least 2m away from equipments which involve electric wave such as televisions, radios or wave clocks, in case electrical interference occurs to such equipment.
 - Avoid locations where curtains, etc., come into contact with the air inlet or air outlet. Curtains, etc., may become dirty or a malfunction may occur.
 - Avoid locations where the unit is exposed to condensation, due to drastic temperature changes. Use under appropriate conditions between 0°C and 35°C in the room.
 - Place on a stable surface with sufficient air circulation.
 - When placing the unit on a heavily carpeted area, it may cause the unit to vibrate slightly.
 - Do not install when there is generation of lamplblack, such as in a kitchen, etc.
- The unit surface may crack.

INSTALLATION SPACE

- It ensures ions full of every corner in the room.




⚠ If the power cord is damaged, it must be replaced by the manufacturer, its service agent, Sharp Authorized Service Centre or similar qualified person in order to avoid hazard.

ENGLISH

FILTER GUIDELINES

- Follow the instructions in this manual for correct care and maintenance of the filter.




- Do not incline the unit.
- When placing the unit on a heavily carpeted area, it may cause the unit to vibrate slightly.

PARTS NAMES


⚠ If the power cord is damaged, it must be replaced by the manufacturer's service agent, Sharp Authorized Service Centre or similar qualified person in order to avoid hazard.

CONTROL PANEL




ILLUSTRATIVE DIAGRAM

FRONT



ILLUSTRATIVE DIAGRAM

BACK



PREPARATION

Be sure to remove the power plug from the wall outlet.



FILTER INSTALLATION

To maintain the quality of the filter, they are installed in the main unit and packed in plastic bag. Be sure to remove the filter from the plastic bag before using the unit.

1 Remove the filter



- 1 Remove the Back Panel.
Pull the tab at the top of the Back Panel.

- 2 Remove the Filter from the plastic bag.





2 Install the filter

- 1 Place the Filter within the main unit with the tab facing towards you.
Do not install filter backwards or the unit will not operate properly.




2 Replace the Back Panel to the main unit.

Push until it clicks into place.




3 Fill in the usage start date on the Date Label.

Use the date as a guide for the filter replacement schedule.




Date Label

MAIN UNIT OPERATION




POWER ON/OFF Button

- Press to start operation (short beep) and stop operation (long beep)



FAN SPEED Button

- Press the FAN SPEED Button to select the desired fan speed. Indicator Lights will show the fan speed currently selected.
- The operation mode can be switched as below.



PLASMACLUSTER ION ON/OFF Button

- Press the PLASMACLUSTER ION ON/OFF Button to turn Plasmaccluster Ion Mode ON and OFF. When Plasmaccluster is ON, the Plasmaccluster Indicator Light will turn on.



To maintain optimum performance of this air purifier, please clean the unit including the filter periodically. When cleaning the unit, be sure to unplug the power cord, and never handle the plug with wet hands. Electric shock and/or bodily injury may occur as a result.

MAIN UNIT

Care cycle 1 month

To prevent dirt or stains on the main unit, clean as often as necessary. If stains are allowed to remain, they may become difficult to remove.

Wipe with a dry, soft cloth

For stubborn stains or dirt, use a soft cloth dampened with warm water to wipe them off.

Do not use volatile fluids

Benzene, paint thinner, polishing powder, etc., may damage the surface.

Do not use detergents

Detergent ingredients may damage the unit.


BACK PANEL

Care cycle 2 weeks

Gently remove dust from the back panel, using a vacuum cleaner or similar tool.

When the back panel has stubborn dirt


- 1 In case of heavy dirt, soak the back panel in water (Approx. 10min.)
Avoid scrubbing the back panel hard when washing.
- 2 Rinse the back panel repeatedly with clean water to remove the solution residue.
- 3 Drip dry filter to remove excess water.



FILTER

Care cycle 3 months

- Remove dust by vacuum cleaner
- Cannot Wash



- Remove the filter, remove dust from the surface by vacuum cleaner.
- For not dirtying the surroundings, please put newspaper under the filter.
- Avoid bending or folding the filter when washing.

CARE AND MAINTENANCE


⚠ When replacing filter, be sure to unplug the power cord, and never handle the plug with wet hands.
Electric shock and/or bodily injury may occur as a result.

FILTER REPLACEMENT GUIDELINES

Filter life varies depending on the room environment, usage, and location of the unit.
If dust or odor persists, replace the filter.

Guide for filter replacement timing

• Up to 2 years after opening *



- Filter materials:
- Filter: Polypropylene
- Frame: Polyester
- Deodorizer: Activated charcoal

CAUTION


- For not dirtying the surroundings, please put newspaper under the purifier when replacing filter.
- Please replace it according to Page E-6&E-7.
- Fill in the usage start date of the filter on the Date Label.
- When you discard filter, you should obey the rubbish classification rules in your residence place.

* Determination for life time of Filter:

Filter life and replacement period is based on the condition of smoking 5 cigarettes per day, reducing the dust collection/deodorization power to half compared with that of new filters, according to Specification of The Japan Electrical Manufacturer's Association JEM1467. The replacement period is about 2 years.
The replacement period differs depending on the operation hours and location of installation.

Multi-Functional HEPA-Deodorizing Filter

Substances can be removed by the filter



- Pollen, airborne allergen (airborne dust mite particles)
- Virus
- Mold
- Dust
- Smell of cigarette (particles)
- Hair of pet

- Smell of cigarette (odor)
- Odor in washroom
- Odor of garbage
- Odor of pet

Substances cannot be removed by the filter

- Hazard gas elements (carbon monoxide in cigarette smoke, etc.)
- The element cause odors frequently

TROUBLESHOOTING

Before calling for service, please review the list below, since the problem may not be a unit malfunction.

SYMPTOM	REMEDY
Odors & smoke difficult to remove	• Check whether the filter is packed in the bag. Please get it out according to the chapter of "Filter Installation" (Refer to E-6-E-7)
The discharged air has an aroma or odor.	• Filter is swiftly dirtied. Please replace the filter. • Plasmacluster Air Purifiers emit small traces of ozone which may produce an odor. These ozone emissions are well within safety levels. • Check to see if the filter is heavily soiled. Clean or replace the filters. If under the strong odors from cigarettes and roasted meat, the filter can cause odors in several weeks or months, so you should replace filters or ventilate the room frequently.
A clicking or ticking sound is heard from the unit.	• Clicking or ticking sounds may be audible when the unit is generating ions. • The sound "click" from generating Plasmacluster Ions varies with environment and modes. Sometimes you cannot hear it, but the effect is the same.

SPECIFICATIONS

Model	FL-V30A-W		
Power Supply	220V-50Hz		
Applicable Floor Area (m ²)	21		
Fan Speed Mode	MAX	MEDIUM	SILENT
Air Flow Volume (m ³ /hour)	180	120	80
Rated Power (W)	35	26	20
Noise Level (dBA)	45	34	23
Dimensions (mm)	356(W)X180(D)X510(H)		
Weight (kg)	~5.0		
Cord Length (m)	2.0		

Replacement Filter

Model: **EZY180S-S-HK**