

SHARP

Be Original.

PN-85TH 1
PN-75TH 1
PN-65TH 1
TOUCHSCREEN LCD MONITOR

4K LCD Panel with Built-in Controller Sets a New Standard in Functionality



BIG PAD

4K
3840 × 2160 Pixels



The PN-85TH1/75TH1/65TH1 is made for show and tell in the digital age. Whatever screen size you choose—85, 75, or 65 inches—you get pristine 4K Ultra-HD resolution. With a pre-installed controller and built-in whiteboard and wireless functionality, it's always ready for a quick meeting. The touchscreen supports up to 20 touch points at a time. You can use either a finger or the bundled touch pen, which gives a Pen-on-Paper writing experience. Your group collaborations just got more seamless and intuitive.

Practical Office Technologies

Cutting-Edge Panel Technology

Supporting 4K Ultra-HD (3,840 × 2,160-pixel) resolution, the LCD panel renders all the texture and detail of images and small text. From architecture to engineering to graphic arts, this monitor excels in demanding professional settings. The panel boasts new optical technology that uses advanced opto-mechanics and signal processing. It differentiates finger and pen input, so you can write and draw on the screen with intuitive ease. An anti-glare film minimises fingerprint soiling and reduces reflections. Even in a brightly lit room, onscreen content is easy to read.

Wireless Connectivity


Wireless LAN and Bluetooth® compatibility allow wire-free connection to multiple devices—including smartphones, tablets, and computers*. No need for tangled wires or conversion adapters. Each device can project images wirelessly to the monitor. You can then capture the wirelessly projected screen and freely add annotations to it using a touch pen.

*Compatible with Windows® and Android™ operating systems



Built-in Controller with IWB Launcher

The PN-85TH1/75TH1/65TH1 has a built-in controller with a new IWB Launcher that makes it easy to operate this all-in-one interactive whiteboard. You don't even need to hook up a dedicated PC. When you start up the main unit, the IWB Launcher is displayed automatically. Simply touch the icons on the desktop for instant access to the features you want to use.



Direct Drawing

Switch to Direct Drawing to use the LCD monitor like a regular whiteboard. Even for first-time users, this simple write-and-erase function is a breeze to operate. You can also save screen captures as PDF files, either on internal storage or on an external storage device.



Simultaneous Writing

The LCD panel recognises up to 20 touch points. Up to four people* at a time can use a finger or touch pen to add their input when inspiration strikes. Meetings, lessons, and brainstorming sessions will come alive.


* With Direct Drawing, only one person at a time can write.

Note: When you use Sharp applications on the built-in controller—including IWB Launcher, Direct Drawing, and Wireless Display—content is displayed at full-HD (1,920 × 1,080-pixel) resolution.

Enhanced Usability

Pen-on-Paper Experience

When the tip of the touch pen glides across the screen, it feels just like a pen on paper. No skips or delays. Instead, you get a smooth and responsive digital ink experience. Whether you choose a 2 mm or a 4 mm tip, the easy-grip bundled touch pen gives you a comfortable writing feel. And thanks to the pen's angular profile, it won't roll away when you put it on a table.




User-Friendly SHARP Pen Software

The easy-to-launch SHARP Pen Software interface has a menu with smartly arranged icons. These give you easy access to pen settings and other useful functions. Further handy functions* include access to cloud storage, an e-mail address book, sticky notes, and bookmarks.

* Availability varies by country/region. For details, please consult your local authorised Sharp dealer or representative.

MFP Connectivity

Scanned documents can be imported directly to SHARP Pen Software from a compatible Sharp MFP. Onscreen image data—including written notes—can be sent to a PC for storage or to an MFP for printing.



Versatile Installation

The PN-85TH1/75TH1/65TH1 is designed to match a diverse range of installation needs. It can be installed in either a landscape or a portrait orientation. With a landscape installation, it can be tilted backwards at 45 degrees or between 0 and 20 degrees*.

* There are restrictions on the tiltable angles and other installation conditions. For details, please consult with your local authorised Sharp dealer or representative.




Quad-Screen Display

By connecting four PCs to the monitor, you can simultaneously display four screens at full-HD. You can easily switch between single-screen and quad-screen modes.

Note: Requires video cables.

SHARP Touch Viewing Software

This touch-operated onscreen user interface lets you easily manipulate different types of files, including Microsoft® Office applications, videos, and web pages. Files are displayed onscreen as “sheets”, which can be stored in onscreen virtual “drawers”. This convenient software adds a fresh touch to business meetings, in-store installations, and more.



SHARP Display Connect

This software supports multifaceted wireless communication. Onscreen content, including handwritten notes, can be shared simultaneously with up to 50 devices. And devices connected to the monitor can exchange files between themselves.

Note: Available via the downloader on the bundled CD-ROM.

4K Interactive Signage

Because it handles the demands of 16/7 operation, the PN-85TH1/75TH1/65TH1 brings reliable daily performance to retail, office, and many other locations.



<System Requirements>

Connected Equipment

| | |
|----------|---|
| Hardware | PC/AT compatible machine with USB 2.0 port (CD-ROM drive required for installation) |
| OS | Windows® 8.1 (32-bit/64-bit), Windows® 10 (32-bit/64-bit) macOS v10.13, macOS v10.14, Google Chrome™ OS v59 or later |

Supplied Software (Windows®)

| | |
|-----------|--|
| CPU | Intel® Core™ i5-6360U or higher Intel® Core™ i7-6650U or higher recommended |
| Memory | 4 GB or more |
| Hard disk | 5 GB or more free space (additional space required for saving data) |


To use the touch panel, connect the bundled USB cable to the computer. The touch panel operates with the standard driver of each OS. On the Mac, operation is only possible in single-touch mode.

Specifications


| Model Name | | PN-85TH1 | PN-75TH1 | PN-65TH1 |
|---|--------------------------------------|--|--|--|
| Installation | | Landscape / Portrait / Backward tilt (0 to 20, 45 degrees)*1 | | |
| LCD Panel | | 85-inch-class [84 ⁹ / ₁₆ inch (214.8 cm) diagonal] TFT LCD | 75-inch-class [74 ¹ / ₂ inch (189.3 cm) diagonal] TFT LCD | 65-inch-class [64 ¹ / ₂ inch (163.9 cm) diagonal] TFT LCD |
| | Max. Resolution | 3,840 × 2,160 pixels | | |
| | Max. Display Colours (approx.) | 1.07 billion colours | | |
| | Pixel Pitch (H x V) | 0.488 × 0.488 mm | 0.430 mm × 0.430 mm | 0.372 × 0.372 mm |
| | Max. Brightness (average)*2 | 350 cd/m ² | | |
| | Contrast Ratio | 5,000 : 1 | | |
| | Viewing Angle (H/V) | 178°/178° (CR ≥10) | | |
| | Active Screen Area (W x H) (approx.) | 1,872 × 1,053 mm (73 ¹¹ / ₁₆ " × 41 ⁷ / ₁₆ ") | 1,650.2 × 928.3 mm (64 ¹⁵ / ₁₆ " × 36 ⁹ / ₁₆ ") | 1,428.5 × 803.5 mm (56 ¹ / ₄ " × 31 ⁵ / ₈ ") |
| | Response Time | 9.5 ms (grey to grey, avg.) | | |
| | Backlight | LED, direct lit | | |
| Touchscreen | Touch Technology | InGlass™ | | |
| | PC Connection Port | USB (2.0 compliant) (Type B) × 2 | | |
| | Power Supply | Supplied from main unit | | |
| | Multi Touch | 20 points | | |
| | Protection Glass | Thickness: Approx. 4 mm Shock resistance: 130 cm | | |
| Computer Input | Video | Analogue RGB (0.7 Vp-p) [75Ω], HDMI™, DisplayPort™ | | |
| | Synchronisation | Horizontal/vertical separation (TTL: positive/negative) | | |
| | Plug & Play | VESA DDC2B | | |
| | Power Management | Supported | | |
| Input Terminals*3 | | PC analogue: Mini D-sub 15-pin × 1, HDMI (HDCP2.2 compatible, HDR10 supported) × 2, 3.5 mm-diameter mini stereo jack × 1, DisplayPort (HDCP compatible) × 1, RS-232 × 1 | | |
| Output Terminals*3 | | 3.5 mm-diameter mini stereo jack × 1, DisplayPort (HDCP compatible) × 1*4 | | |
| Controller | CPU | Hexa Core [Arm® Cortex®-A72 processor (dual core) + Arm Cortex-A53 processor (quad core)] | | |
| | Memory | 4 GB | | |
| | Storage | 32 GB | | |
| | External Interface | LAN port (10Base-T/100Base-TX/1000Base-T), microSD card slot (microSD/microSDHC/microSDXC [®]) × 1, USB port (3.0-compliant) × 2, USB port (2.0-compliant) × 1 | | |
| | Wireless LAN | Compliant with IEEE802.11ac/n/a/g/b | | |
| | Bluetooth | Compliant with version 4.1 (A2DP/AVRCP/GATT/GAP/HID/HOGP) | | |
| USB Hub Function | | USB port (2.0-compliant) × 2 | | |
| Expansion Slot | | 12 V, 2.5 A (power supplied when expanding the functions with an optional part) | | |
| Speaker Output | Built-in | 10 W + 10 W | | |
| | External | 10 W + 10 W (6 Ω) | | |
| Mounting | | 4 points, 600 × 400 mm pitch, M6 screw | | 4 points, 400 × 400 mm pitch, M6 screw |
| Power Supply*5 | | 100V – 240 V AC, 50/60 Hz | | |
| Power Consumption | | 310 W | 330 W | 270 W |
| Environmental Conditions | Operating Temperature*7*8 | 5° C to 35° C | | |
| | Operating Humidity*8 | 20% to 80% RH (no condensation) | | |
| Dimensions (W x D x H) (approx.) (display only) | | 1,951 × 99 × 1,150 mm (76 ¹³ / ₁₆ " × 3 ⁷ / ₈ " × 45 ¹ / ₄ ") | 1,724 × 98 × 1,020 mm (67 ⁷ / ₈ " × 3 ⁷ / ₈ " × 40 ³ / ₁₆ ") | 1,501 x 98 x 894 mm (59 ³ / ₈ " × 3 ⁷ / ₈ " × 35 ³ / ₁₆ ") |
| Weight (approx.) | | 77 kg (170 lbs) | 61 kg (135 lbs) | 48 kg (106 lbs) |
| Main Accessories | | AC power cord, remote control unit, remote control unit battery (AAA size) × 2, set-up manual, speaker cover × 2, vertical sticker, blank sticker, cable clamp × 5, camera mount, USB cable, eraser, pen tray, SHARP Pen Software (CD-ROM), touch pen (PN-85TH1 × 2, PN-75TH1/65TH1 × 1), SHARP Display Connect license, Wireless LAN antenna × 2, USB flash drive/microSD card cover, USB flash drive/microSD card cover fixing screw | | |

*1 There are restrictions on the tiltable angles and other installation conditions. For details, please consult with your local authorised Sharp dealer or representative. *2 Brightness depends on input mode and other picture settings. Brightness level will decrease slightly over the lifetime of the product. Due to the physical limitations of the equipment, it is not possible to maintain a precisely constant level of brightness. *3 Use a commercially available connection cable for PC and other video connections. *4 Use a commercially available DisplayPort-certified cable. Some video equipment may not be supported. *5 exFAT is not supported. *6 The AC power cord is an inlet type. The cable is bundled (3 pins) *7 When the monitor is tilted more than 20 degrees upward from the perpendicular in relation to a level surface, the ambient temperature must be within the range of 5°C to 30°C. *8 Check the requirements of the computer and other devices to be connected, and make sure that all requirements are satisfied.

Dimensions



Input/Output Terminals



Bluetooth is a registered trademark of Bluetooth SIG, Inc. Windows and Microsoft® Office are registered trademarks of Microsoft Corporation. Google Chrome and Android trademarks of Google LLC. macOS is a trademark of Apple Inc., registered in the U.S. and other countries. Intel and Intel Core are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. FLATFROG, the FLATFROG logo, and INGLASS are trademarks of FlatFrog Laboratories AB registered in the United States and other regions. The terms HDMI, HDMI High-Definition Multimedia Interface and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. DisplayPort Compliance Logo are trademarks owned by the Video Electronics Standards Association in the United States and other countries. Arm and Cortex are registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. All other brand names and product names may be trademarks or registered trademarks of their respective owners. All screen images appearing in this brochure are simulated. Design and specifications are subject to change without prior notice.



Distributed by:

